

GTEC Intumescent Acoustic Sealant

No. UKSI-15651-001-19

1. Unique identification code of the product-type:

GTEC Intumescent Acoustic Sealant, GTEC Foil Roll Intumescent Acoustic sealant

Type F-INT

Class F7.5P

2. Intended use/es:

General building construction

3. Manufacturer:

Siniat, Etex Building Performance Limited, Marsh Lane, Easton-in-Gordano, Bristol, BS20 ONE, UK

4. Not applicable

5. System/s of AVCP:

System 4

6a. Harmonised standard: EN 15651-1:2012

Notified Body/ies: n/a

7. Declared performance/s:

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to Fire	Class F	BS EN 15651-1: 2012
Watertightness and airtightness		
a) resistance to flow	≤5mm	BS EN 15651-1: 2012
b) loss of volume	≤ 45%	BS EN 15651-1: 2012
c) tensile properties – at break at (23°C)	≥ 25%	BS EN 15651-1: 2012
Durability	Pass	BS EN 15651-1: 2012

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Singed for on behalf of Etex Building Performance Limited by: Nigel Morrey, Technical director Bristol, UK, 15/08/2019



Please check that this is the current version by visiting the Siniat website. For archived versions please contact technical services.

