

DECLARATION OF PERFORMANCE SINIAT LADURA



No.UKSI-00520-011-22GB

 ${\bf 1.}\ Unique\ identification\ code\ of\ the\ product-type:$

Siniat Ladura (Gypsum plasterboard type D, E, F, H1, I, R)

2. Intended use/es:

General building construction

3. Manufacturer:

Siniat, Etex Building Performance Limited, Marsh Lane, Easton-in-Gordano, Bristol, BS20 ONE, UK

4. Not applicable

5. System/s of AVCP:

System 4

6a. Designated standard: EN 520:2004+A1:2009

Notified/Approved Body: N/A Performed: N/A Under: N/A

6b. **N/A**

7. Declared performance/s:

Essential Characteristics	Performance		Harmonised Technical Specification
Shear strength-	ı	NPD	
Reaction to fire - R2F:	A2-	-s1,d0	EN520:2004+A1:2009
Water vapour permeability - μ:		10	EN 12514:2000
Flexural strength - F: 12.5mm 15mm	Transverse 300 N 360 N	Longitudinal 725 N 870 N	EN 520:2004+A1:2009
Thermal resistance - λ:	0.25	W/m.K	EN 12524:2000
Impact Resistance- →I:	see lit	terature	
Airborne sound insulation - R:	see lit	terature	
Acoustic absorption - α:	see lit	terature	

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, as it has effect in the United Kingdom, in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of Etex Building Performance Limited by: Nigel Morrey, Technical Director Bristol, UK, 01/11/2022



Please check that this is the current version by visiting the Siniat website. For archived versions please contact Technical Services.

