

DECLARATION OF PERFORMANCE SINIAT LADURA



No.UKSI-00520-011-24GB

 ${\bf 1.}\ {\bf Unique\ identification\ code\ of\ the\ product-type:}$

Siniat LaDura (Gypsum plasterboard type D, F, H1, I, R)

2. Intended use/es:

General building construction

3. Manufacturer:

Siniat, Etex Building Performance Limited, Marsh Lane, Easton-in-Gordano, Bristol, BS20 ONE, UK

4. Not applicable

5. System/s of AVCP:

System 4

6a. Designated standard: EN 520:2004+A1:2009

Approved Body: N/A Performed: N/A Under: N/A

6b. N/A

7. Declared performance/s:

Essential Characteristics	Performance		Harmonised Technical Specification
Shear strength- ↓↑	NPD		
Reaction to fire - R2F:	A2-s1,d0		EN520:2004+A1:2009
Water vapour permeability - μ:	10		EN 12524:2000
Flexural strength - F:	Transverse	Longitudinal	
12.5mm	300 N	725 N	EN 520:2004+A1:2009
15mm	360 N	870 N	
Thermal resistance - λ:	0.25 W/m.K		EN 12524:2000
Impact Resistance- →I:	see literature		
Airborne sound insulation - R:	see literature		
Acoustic absorption - α:	see literature		

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, as it has effect in the United Kingdom, in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of Etex Building Performance Limited by:

Nigel Morrey, Technical Director

Bristol, UK, 29/10/2024

Please check that this is the current version by visiting the Siniat website. For archived versions please contact technical services.

