

DECLARATION OF PERFORMANCE SINIAT FIRE MR BOARD



No.UKSI-00520-013-22GB

1. Unique identification code of the product-type:

Siniat Fire MR Board (Gypsum plasterboard type D, F, H2)

2. Intended use/es:

General building construction

3. Manufacturer:

Siniat, Etex Building Performance Limited, Marsh Lane, Easton-in-Gordano, Bristol, BS20 ONE, UK

4. Not applicable

5. System/s of AVCP:

System 4

6a. Designated standard: EN 520:2004+A1:2009

Approved Body: N/A Performed: N/A Under: N/A

6b. N/A

7. Declared performance/s:

Essential Characteristics	Performance	Harmonised Technical Specification
Flexural strength - F:	Transverse Longitudinal	
12.5mm	≥210N ≥550N	EN 520:2004+A1:2009
15mm	≥250N ≥650N	
Shear strength- ↓↑	NPD	
Reaction to fire - R2F:	A2,-s1,d0	EN 520:2004+A1:2009
Airborne sound insulation - R:	see literature	
Acoustic absorption - α:	see literature	
Water vapour permeability - μ:	10	EN 12524:2000
Thermal conductivity - λ:	0.25 W/m.K	EN 12524:2000
Impact Resistance- →I:	see literature	

8. Appropriate Technical Documentation and/or Specific Technical Documentation:

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, as it has effect in the United Kingdom, in respect of Great Britain, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of Etex Building Performance Limited by: Nigel Morrey, Technical Director

Bristol, UK, 04/10/2022

2

Please check that this is the current version by visiting the Siniat website. For archived versions please contact technical services.

